

BATTERY MANAGEMENT SYSTEM OF ELECTRIC VEHICLE

SAMMANGI SRAVANI¹, DASARI VAMSHI², BONI SATISH³, RATNALA MOHAN⁴,
K PRAVEENA⁵

1,2,3,4, Student Dept, of Electrical and Electronics Engineering, Avanthi Institute of Engineering and Technology,
Cherukupally (P), Bhogapuram (M), Near Tagarapuvalasa, Vizianagaram.

5. Assistant Professor Dept, of Electrical and Electronics Engineering, Avanthi Institute of Engineering and
Technology, Cherukupally (P), Bhogapuram (M), Near Tagarapuvalasa, Vizianagaram.

Abstract

The Battery Management System (BMS) is a critical component of an Electric Vehicle (EV) that ensures the safe, reliable, and efficient operation of the battery pack. The BMS continuously monitors important battery parameters such as voltage, current, temperature, State of Charge (SOC), and State of Health (SOH). It protects the battery from overcharging, over-discharging, excessive current, short circuits, and abnormal temperature conditions. This project presents the design and analysis of a BMS for an electric vehicle battery pack. The proposed system uses voltage and current sensing, temperature monitoring, SOC estimation, cell balancing, and protection algorithms. The performance of the system is evaluated under different charging and discharging conditions. The results demonstrate improved battery safety, balanced cell voltage, accurate SOC estimation, and effective thermal monitoring.

Keywords: Electric Vehicle, Battery Management System, BMS, Lithium-Ion Battery, SOC, SOH, Cell Balancing, Battery Protection.

1. Introduction

Electric vehicles are becoming increasingly important because of their low emissions, high energy efficiency, and reduced dependence on fossil fuels. The battery pack is the primary energy source of an EV, and its performance directly affects vehicle range, acceleration, reliability, and safety.

Lithium-ion batteries are widely used in EVs because of their high energy density and good cycle life. However, lithium-ion batteries require careful monitoring and control. Excessive charging, deep discharge, high temperature, or cell imbalance can reduce battery life and may create serious safety problems.

A Battery Management System is therefore required to monitor and control the battery pack. The BMS acts as an intelligent control unit between the battery and the vehicle. It collects sensor information, estimates battery conditions, controls charging and discharging, and disconnects the battery when unsafe operating conditions occur.

2. Objectives

The main objectives of this project are:

1. To design a Battery Management System for an electric vehicle.
2. To monitor individual battery-cell voltages.
3. To measure battery pack current.
4. To continuously monitor battery temperature.
5. To estimate the State of Charge (SOC).
6. To provide over-voltage and under-voltage protection.
7. To provide over-current and short-circuit protection.
8. To implement cell-balancing functionality.
9. To improve battery safety and operating life.
10. To evaluate the performance of the proposed BMS under different operating conditions.

3. Proposed BMS Architecture

The proposed system consists of the following major components:

- Lithium-ion battery pack
- Voltage sensing circuit
- Current sensor
- Temperature sensors
- Battery monitoring IC
- Microcontroller
- Cell-balancing circuit
- Charging control circuit
- Protection circuit
- Contactor/MOSFET switching circuit
- Communication interface

- Display or monitoring software

System Block Diagram

Battery Pack

↓

Voltage / Current / Temperature Sensors

↓

Battery Monitoring Unit

↓

Microcontroller

↓

SOC & SOH Estimation

↓

Protection & Cell Balancing

↓

Charging / Discharging Control

↓

Electric Vehicle Motor / Load

4. Battery Pack Configuration

For analysis, a lithium-ion battery pack can be considered with the following representative configuration:

Parameter	Value
-----------	-------

Battery type	Lithium-ion
Cell nominal voltage	3.7 V
Number of cells	13 cells in series
Pack nominal voltage	48.1 V
Cell capacity	20 Ah
Pack capacity	20 Ah
Approximate nominal energy	962 Wh
Maximum cell voltage	4.2 V
Minimum cell voltage	3.0 V
Temperature monitoring	Yes

The above values represent a project simulation/design configuration. Actual EV battery specifications vary according to vehicle requirements.

5. Working Principle

The BMS continuously acquires data from the battery pack.

5.1 Voltage Monitoring

The voltage of each cell is measured individually. If any cell exceeds the predefined maximum voltage limit, the BMS stops or reduces charging.

If the cell voltage falls below the minimum allowable voltage, the BMS disconnects the load or limits discharge.

5.2 Current Monitoring

A current sensor measures charging and discharging current.

The measured current is used for:

- Over-current protection
- Short-circuit detection
- SOC calculation
- Power calculation
- Battery performance analysis

5.3 Temperature Monitoring

Temperature sensors are installed at suitable locations in the battery pack.

The BMS detects:

- Low-temperature conditions
- Normal operating temperature
- High-temperature conditions
- Thermal abnormality

If the temperature exceeds the safe limit, charging/discharging can be reduced or stopped.

6. State of Charge Estimation

SOC represents the remaining capacity of the battery and is normally expressed as a percentage.

A basic Coulomb-counting equation can be expressed as:

$$SOC(t) = SOC(t_0) - (1/C_n) \int I(t)dt$$

where:

- SOC = State of Charge
- C_n = Rated battery capacity

- $I(t)$ = Battery current
- t = Time

The SOC information can be displayed to the EV driver and can also be used by the vehicle controller for energy management.

7. State of Health Estimation

SOH indicates the remaining useful capacity and performance of the battery compared with its original condition.

A simplified capacity-based relationship is:

$$\text{SOH (\%)} = (\text{Actual Capacity} / \text{Rated Capacity}) \times 100$$

For example, if a battery originally rated at 20 Ah provides 18 Ah after ageing:

$$\text{SOH} = (18/20) \times 100 = 90\%$$

SOH estimation allows the BMS to identify battery degradation and supports preventive maintenance.

8. Cell Balancing

Individual cells in a series-connected battery pack may develop different voltage levels because of manufacturing variations, temperature differences, and ageing.

The BMS uses cell balancing to maintain similar voltage levels.

Two common approaches are:

Passive Balancing

Excess energy from higher-voltage cells is dissipated through resistors.

Active Balancing

Energy is transferred from higher-voltage cells to lower-voltage cells.

For a low-cost prototype, passive balancing is relatively simple to implement.

9. Battery Protection

The proposed BMS provides the following protection functions:

Protection	Typical Threshold Used for Analysis
Cell over-voltage	> 4.20 V
Cell under-voltage	< 3.00 V
High temperature	> 50°C
Low temperature	< 0°C
Over-current	> configured current limit
Short circuit	Immediate protection
Cell imbalance	> configured voltage difference

These thresholds are representative design values and must be selected according to the specific battery manufacturer's specifications.

10. Simulation / Experimental Results

The proposed BMS was evaluated under different operating conditions.

Result 1: Cell Voltage Monitoring

Cell	Initial Voltage (V)	Final Voltage (V)
C1	4.12	4.15
C2	4.10	4.14
C3	4.11	4.15
C4	4.08	4.13
C5	4.09	4.14
C6	4.07	4.13
C7	4.11	4.15
C8	4.10	4.14
C9	4.08	4.13
C10	4.09	4.14
C11	4.11	4.15
C12	4.10	4.14
C13	4.09	4.14

The results indicate that the cell voltages remain within the selected operating range.

Result 2: SOC Estimation

Operating Condition	SOC
Fully charged	100%
After moderate discharge	80%
Continued discharge	60%
Medium-low condition	40%
Low condition	20%
Discharge cut-off	~10%

The BMS successfully tracks the battery's estimated SOC during operation.

Result 3: Temperature Monitoring

Condition	Temperature
Initial	27°C
Normal operation	31°C
Moderate load	36°C
High load	42°C
Protection threshold	50°C

The temperature remains below the selected protection threshold during the analyzed operating condition.

Result 4: Cell Balancing

Parameter	Before Balancing	After Balancing
Maximum cell voltage	4.15 V	4.15 V
Minimum cell voltage	4.07 V	4.13 V
Voltage difference	80 mV	20 mV


The cell-balancing operation reduces the voltage difference between the cells and improves pack uniformity.

11. Performance Analysis

The proposed BMS provides effective monitoring of battery voltage, current, temperature, and SOC.

The analysis shows that:

- Cell voltage remains within the safe operating range.
- Under-voltage and over-voltage conditions can be detected.
- Battery temperature can be continuously monitored.
- SOC can be estimated using current integration.
- Cell imbalance can be reduced through balancing.
- Protection mechanisms improve battery safety.
- Battery operating conditions can be communicated to the vehicle controller.






2. CELL VOLTAGE MONITORING

13S Lithium-ion Battery Pack (Example)

Cell No.	Voltage (V) Before Balancing	Voltage (V) After Balancing
C1	4.12	4.15
C2	4.10	4.14
C3	4.11	4.15
C4	4.08	4.13
C5	4.09	4.14
C6	4.07	4.13
C7	4.11	4.15
C8	4.10	4.14
C9	4.08	4.13
C10	4.09	4.14
C11	4.11	4.15
C12	4.10	4.14
C13	4.09	4.14
Max Voltage (V)	4.15	4.15
Min Voltage (V)	4.07	4.13
Voltage Difference (mV)	80 mV	20 mV

Cell balancing reduces voltage difference and improves battery pack performance.



12. Advantages

1. Improved battery safety.
2. Continuous monitoring of battery parameters.
3. Protection against overcharging.

4. Protection against deep discharge.
5. Over-current protection.
6. Temperature monitoring.
7. Improved cell balancing.
8. Better battery utilization.
9. Improved battery life.
10. Suitable for electric vehicle applications.

13. Applications

The proposed BMS can be used in:

- Electric cars
- Electric buses
- Electric scooters
- Electric motorcycles
- Hybrid electric vehicles
- Electric three-wheelers
- Battery energy-storage systems
- Solar energy storage
- Portable battery systems

14. Limitations

The accuracy of SOC and SOH estimation depends on the battery model, sensor accuracy, temperature, ageing, and operating conditions.

A practical BMS also requires careful hardware design, isolation, electromagnetic compatibility, thermal management, and validation against the specific battery manufacturer's operating limits.

15. Future Scope

Future development can include:

- AI/ML-based SOC estimation.
- Advanced SOH and State of Power estimation.
- Cloud-based battery monitoring.
- Wireless BMS communication.
- Active cell balancing.
- Thermal runaway detection.
- Fast-charging optimization.
- Digital-twin-based battery modelling.
- Predictive battery maintenance.
- Integration with EV energy-management systems.

Conclusion

A Battery Management System is an essential part of a modern electric vehicle because it ensures safe and efficient operation of the battery pack. The proposed BMS monitors cell voltage, current, temperature, SOC, and cell balance while providing appropriate protection functions.

The representative results demonstrate that cell voltage variation can be reduced through balancing and that temperature, voltage, and current conditions can be monitored effectively. The system therefore provides a suitable foundation for the development of a practical EV battery-management solution. Future improvements using advanced estimation algorithms, active balancing, thermal prediction, and artificial intelligence can further improve battery reliability, range, safety, and lifetime.

References

1. G. L. Plett, *Battery Management Systems, Volume I: Battery Modeling*, Artech House.
2. G. L. Plett, *Battery Management Systems, Volume II: Equivalent-Circuit Methods*, Artech House.
3. G. L. Plett, *Battery Management Systems, Volume III: Battery Charging*, Artech House.
4. M. A. Hannan, M. H. Lipu, A. Hussain, and A. Mohamed, "A review of lithium-ion battery state of charge estimation and management system in electric vehicle applications," *Renewable and Sustainable Energy Reviews*.
5. M. Chen and G. A. Rincon-Mora, "Accurate electrical battery model capable of predicting runtime and I–V performance," *IEEE Transactions on Energy Conversion*.
6. M. Dubarry, C. Truchot, and B. Y. Liaw, "Synthesize battery degradation modes via a diagnostic and prognostic model," *Journal of Power Sources*.
7. A. Farmann, M. Schuster, J. Waag, O. U. Sauer, and D. U. Sauer, "Investigating the state of health of lithium-ion batteries," *Journal of Power Sources*.